



SECTION 1: IDENTIFICATION OF THE PRODUCT AND OF THE COMPANY

1.1 Product identifiers

Product Name : ACS Material Monolayer WSe₂ on SiO₂
Substrate
Brand : ACS Material LLC
CAS-No. : 12067-46-8 (WSe₂); 60676-86-0 (SiO₂)

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses : Laboratory chemicals, Manufacture of substances

1.3 Details of the supplier of the safety data sheet

Company : ACS MATERIAL LLC
43 Riverside Avenue, Suite 472
Medford, MA 02155-2213
USA
Telephone : +1 (866)-227-0656
Fax : +1 (781)-518-0284

1.4 Emergency telephone number

Emergency Phone #: +1 (866)-227-0656

SECTION 2: HAZARDS IDENTIFICATION

2.1 Classification of the substance or mixture**GHS Classification in accordance with 29 CFR 1910 (OSHA HCS)**

Acute toxicity, Oral (Category 3), H301

Acute toxicity, Inhalation (Category 3), H331

Specific target organ toxicity - repeated exposure (Category 2), H373

Acute aquatic toxicity (Category 1), H400

Chronic aquatic toxicity (Category 1), H410

For the full text of the H-Statements mentioned in this Section, see Section 16.

2.2 GHS Label elements, including precautionary statements

Pictogram



Signal word

Danger



Hazard statement(s)

- H301 + H331 Toxic if swallowed or if inhaled
- H373 May cause damage to organs through prolonged or repeated exposure.
- H410 Very toxic to aquatic life with long lasting effects.

Precautionary statement(s)

- P260 Do not breathe dust/ fume/ gas/ mist/ vapours/ spray.
- P264 Wash skin thoroughly after handling.
- P270 Do not eat, drink or smoke when using this product.
- P271 Use only outdoors or in a well-ventilated area.
- P273 Avoid release to the environment.
- P301 + P310 + P330 IF SWALLOWED: Immediately call a POISON CENTER/doctor.
Rinse mouth.
- P304 + P340 + P311 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/doctor.
- P314 Get medical advice/ attention if you feel unwell.
- P391 Collect spillage.
- P403 + P233 Store in a well-ventilated place. Keep container tightly closed.
- P405 Store locked up.
- P501 Dispose of contents/ container to an approved waste disposal plant.

2.3 Hazards not otherwise classified (HNOC) or not covered by GHS

None.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1 Substances

Substance name : ACS Material Monolayer WSe₂ on SiO₂
Substrate



CAS-No	:	12067-46-8
Synonyms	:	Tungsten (IV) selenide Tungsten selenide
Molecular weight	:	341.76 g/mol
Linear formula	:	WSe ₂
CAS-No	:	60676-86-0
Synonyms	:	Silica Quartz Sand Cristobalite
Molecular weight	:	60.08 g/mol
Linear formula	:	SiO ₂

Hazardous ingredients

Chemical characterization: Tungsten diselenide, crystalline, synthetic, non-fibrous

Components	Concentration	CAS No.
Tungsten diselenide	<=100%	12067-46-8

For the full text of the phrases mentioned in this Section, see Section 16.

Hazardous impurities: None known.

SECTION 4: FIRST AID MEASURES**4.1 Description of first aid measures****General advice**

Consult a physician. Show this safety data sheet to the doctor in attendance. Move out of dangerous area.

If inhaled

If breathed in, move person into fresh air. If not breathing, give artificial respiration. Consult a physician.

In case of skin contact

Wash off with soap and plenty of water. Take victim immediately to hospital. Consult a physician.

In case of eye contact

Rinse thoroughly with plenty of water for at least 15 minutes and consult a physician.

If swallowed

Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Rinse mouth with water. Consult a physician.

4.2 Most important symptoms and effects, both acute and delayed

The most important known symptoms and effects are described in the labelling (see section 2.2) and/or in section 11.



- 4.3 Indication of any immediate medical attention and special treatment needed**
No data available.

SECTION 5: FIREFIGHTING MEASURES

5.1 Extinguishing media

Suitable extinguishing media

Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.

5.2 Special hazards arising from the substance or mixture

Silicon oxides.

5.3 Advice for firefighters

Wear self-contained breathing apparatus for firefighting if necessary.

5.4 Further information

No data available.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures

Wear respiratory protection. Avoid dust formation. Avoid breathing vapours, mist or gas. Ensure adequate ventilation. Evacuate personnel to safe areas. Avoid breathing dust.

For personal protection see section 8.

6.2 Environmental precautions

Prevent further leakage or spillage if safe to do so. Do not let product enter drains. Discharge into the environment must be avoided.

6.3 Methods and materials for containment and cleaning up

Pick up and arrange disposal without creating dust. Sweep up and shovel. Keep in suitable, closed containers for disposal.

6.4 Reference to other sections

For disposal see section 13.

SECTION 7: HANDLING AND STORAGE

7.1 Precautions for safe handling

Suitable extinguishing media

Avoid contact with skin and eyes. Avoid formation of dust and aerosols. Further processing of solid materials may result in the formation of combustible dusts. The potential for combustible dust formation should be taken into consideration before additional processing occurs.

Provide appropriate exhaust ventilation at places where dust is formed.

For precautions see section 2.2.

**7.2 Conditions for safe storage, including any incompatibilities**

Store in cool place. Keep container tightly closed in a dry and well-ventilated place.

Air-, heat-, and moisture-sensitive. Store under nitrogen. Recommended storage temperature 2 - 8 °C.

Substrate: strongly hygroscopic. Storage class (TRGS 510): Non Combustible Solids

7.3 Specific end use(s)

Apart from the uses mentioned in section 1.2 no other specific uses are stipulated.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION**8.1 Control parameters****Components with workplace control parameters**

Components	CAS-No.	Value	Control Parameters	Basis
Tungsten diselenide	12067-46-8	TWA	0.2 mg/m ³	USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants
		TWA	0.2 mg/m ³	USA. ACGIH Threshold Limit Values (TLV)
	Remarks	Upper Respiratory Tract irritation Eye irritation		
		TWA	5 mg/m ³	USA. ACGIH Threshold Limit Values (TLV)
		Lower Respiratory Tract irritation varies.		
		STEL	10 mg/m ³	USA. ACGIH Threshold Limit Values (TLV)
		Lower Respiratory Tract irritation varies.		
		TWA	0.2 mg/m ³	USA. NIOSH Recommended Exposure Limits
		TWA	5 mg/m ³	USA. NIOSH Recommended Exposure Limits
		ST	10 mg/m ³	USA. NIOSH Recommended Exposure Limits
		PEL	0.2 mg/m ³	California permissible exposure limits for chemical contaminants (Title 8, Article 107)
		PEL	5 mg/m ³	California permissible exposure limits for chemical contaminants (Title 8, Article 107)
		STEL	10 mg/m ³	California permissible exposure



				limits for chemical contaminants (Title 8, Article 107)
--	--	--	--	--

8.2 Exposure controls

Appropriate engineering controls

Avoid contact with skin, eyes and clothing. Wash hands before breaks and immediately after handling the product.

8.3 Personal protective equipment

Eye/face protection

Face shield and safety glasses Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU).

Skin protection

Handle with gloves. Gloves must be inspected prior to use. Use proper glove removal technique (without touching glove's outer surface) to avoid skin contact with this product. Dispose of contaminated gloves after use in accordance with applicable laws and good laboratory practices.

Wash and dry hands.

Full contact

Material: Nitrile rubber

Minimum layer thickness: 0.11 mm

Break through time: 480 min

Material tested: Dermatrill® (KCL 740 / Aldrich Z677272, Size M)

Splash contact

Material: Nitrile rubber

Minimum layer thickness: 0.11 mm

Break through time: 480 min

Material tested: Dermatrill® (KCL 740 / Aldrich Z677272, Size M)

Data source: KCL GmbH, D-36124 Eichenzell, phone +49 (0)6659 87300, e-mail sales@kcl.de,

test method: EN374

If used in solution, or mixed with other substances, and under conditions which differ from EN 374, contact the supplier of the CE approved gloves. This recommendation is advisory only and must be evaluated by an industrial hygienist and safety officer familiar with the specific situation of anticipated use by our customers. It should not be construed as offering an approval for any specific use scenario.

Body Protection

Complete suit protecting against chemicals recommended. The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.

Respiratory protection

Where risk assessment shows air-purifying respirators are appropriate use a full-face particle respirator type N99 (US) or type P2 (EN 143) respirator cartridges as a backup



to engineering controls. If the respirator is the sole means of protection, use a full-face supplied air respirator. Use respirators and components tested and approved under appropriate government standards such as NIOSH (US) or CEN (EU).

Control of environmental exposure

Prevent further leakage or spillage if safe to do so. Do not let product enter drains. Discharge into the environment must be avoided.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties

1) Appearance	Form: crystalline Colour: metallic
2) Odour	No data available
3) Odour Threshold	No data available
4) pH	No data available
5) Melting point/freezing point	Melting point/range: 1,200 °C (2,192 °F)
6) Initial boiling point and boiling range	No data available
7) Flash point	No data available
8) Evaporation rate	No data available
9) Flammability (solid, gas)	No data available
10) Upper/lower flammability or explosive limits	No data available
11) Vapour pressure	No data available
12) Vapour density	No data available
13) Relative density	No data available
14) Water solubility	No data available
15) Partition coefficient: n- octanol/water	No data available
16) Auto-ignition temperature	No data available
17) Decomposition temperature	No data available
18) Viscosity	No data available
19) Explosive properties	No data available
20) Oxidizing properties	No data available

9.2 Other safety information

Bulk density(SiO₂) 480 - 600 kg/m³

SECTION 10: STABILITY AND REACTIVITY

10.1 Reactivity

No data available.

10.2 Chemical stability

Stable under recommended storage conditions.

**10.3 Possibility of hazardous reactions**

No data available.

10.4 Conditions to avoid

No data available.

10.5 Incompatible materials

Strong oxidizing agents.

10.6 Hazardous decomposition products

Hazardous decomposition products formed under fire conditions. - Tungsten oxide, Selenium/selenium oxides.

Other decomposition products - No data available

In the event of fire: see section 5.

SECTION 11: TOXICOLOGICAL INFORMATION

11.1 Information on toxicological effects**Acute toxicity****WSe₂:**

No data available.

Inhalation: No data available.

Dermal: No data available.

No data available.

SiO₂:

LD50 Oral - rat - > 5,000 mg/kg

Inhalation: no data available

Dermal: no data available

Skin corrosion/irritation

No data available.

Serious eye damage/eye irritation

No data available.

Respiratory or skin sensitisation

No data available.

Germ cell mutagenicity

No data available.

Carcinogenicity

IARC: No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

NTP: No component of this product present at levels greater than or equal to 0.1% is



identified as a known or anticipated carcinogen by NTP.

OSHA: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

Reproductive toxicity

No data available.

Specific target organ toxicity - single exposure

No data available.

Specific target organ toxicity - repeated exposure

No data available

Aspiration hazard

No data available

Additional Information

RTECS: YO7714000

To the best of our knowledge, the chemical, physical, and toxicological properties of WSe₂ have not been thoroughly investigated.

SECTION 12: ECOLOGICAL INFORMATION

12.1 Toxicity

No data available.

12.2 Persistence and degradability

No data available.

12.3 Bioaccumulative potential

No data available.

12.4 Mobility in soil

No data available.

12.5 Results of PBT and vPvB assessment

PBT/vPvB assessment not available as chemical safety assessment not required/not conducted.

12.6 Other adverse effects

An environmental hazard cannot be excluded in the event of unprofessional handling or disposal. Very toxic to aquatic life with long lasting effects.

SECTION 13: DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods

Product

Offer surplus and non-recyclable solutions to a licensed disposal company. Contact a licensed professional waste disposal service to dispose of this material. Dissolve or mix the material with a combustible solvent and burn in a chemical incinerator equipped with an afterburner and



scrubber.

Contaminated packaging

Dispose of as unused product.

SECTION 14: TRANSPORT INFORMATION

UN number

ADR/RID: 3283

IMDG: 3283

IATA: 3283

UN proper shipping name

ADR/RID: Selenium compound, solid, n.o.s. (Tungsten diselenide)

IMDG: SELENIUM COMPOUND, SOLID, N.O.S. (Tungsten diselenide)

IATA: Selenium compound, solid, n.o.s. (Tungsten diselenide)

Transport hazard class(es)

ADR/RID: 6.1

IMDG: 6.1

IATA: 6.1

Packaging group

ADR/RID: III

IMDG: III

IATA: III

Environmental hazards

ADR/RID: No data available.

IMDG Marine pollutant: yes

IATA: No data available.

Special precautions for user

No data available.

SECTION 15: REGULATORY INFORMATION

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**Authorisations and/or restrictions on use****SARA 302 Components**

No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

SARA 313 Components

The following components are subject to reporting levels established by SARA Title III, Section 313:



Tungsten diselenide	CAS-No. 12067-46-8	Revision Date 2007-07-01
---------------------	-----------------------	-----------------------------

SARA 311/312 Hazards

Acute Health Hazard.

Massachusetts Right To Know Components

No components are subject to the Massachusetts Right to Know Act.

Pennsylvania Right To Know Components

Tungsten diselenide	CAS-No. 12067-46-8	Revision Date 2007-07-01
---------------------	-----------------------	-----------------------------

Silicon dioxide

-

New Jersey Right To Know Components

Tungsten diselenide	CAS-No. 12067-46-8	Revision Date 2007-07-01
---------------------	-----------------------	-----------------------------

Silicon dioxide

-

California Prop. 65 Components

This product does not contain any chemicals known to State of California to cause cancer, birth defects, or any other reproductive harm.

SECTION 16: OTHER INFORMATION**Full text of H-Statements referred to under sections 2 and 3.**

Acute Tox.	Acute toxicity
Aquatic Acute	Acute aquatic toxicity
Aquatic Chronic	Chronic aquatic toxicity
H301	Toxic if swallowed.
H301 + H331	Toxic if swallowed or if inhaled
H331	Toxic if inhaled.
H373	May cause damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.

HMIS Classification

Health hazard:	2
Chronic Health Hazard:	
Flammability:	0
Physical Hazard:	0

NFPA Rating

Health hazard:	2
Fire Hazard:	0
Reactivity Hazard:	0



Disclaimer: ACS Material, LLC believes that the information in this Safety Data Sheet is accurate and represents the best and most current information available to us. ACS Material makes no representations or warranties either express or implied, regarding the suitability of the material for any purpose or the accuracy of the information contained within this document. Accordingly, ACS Material will not be responsible for damages resulting from use of or reliance upon this information.