Version: 1.2 / EN

Revision Date: 08/22/2017

#### SECTION 1: IDENTIFICATION OF THE PRODUCT AND OF THE COMPANY

1.1 Product identifiers

Product Name: ACS Material Upconverting Nanoparticles

Brand : ACS Material LLC

CAS-No. : 7681-49-4(Sodium fluoride), 64-17-5(Ethanol)

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses : Laboratory chemicals, Manufacture of substances

1.3 Details of the supplier of the safety data sheet

Company : ACS MATERIAL LLC

959 E Walnut St., Suite 100

Pasadena, CA 91106

USA

Telephone : +1 (866)-227-0656 Fax : +1 (781)-518-0284

1.4 Emergency telephone number

Emergency Phone #: +1 (866)-227-0656

#### **SECTION 2: HAZARDS IDENTIFICATION**

#### 2.1 Classification of the substance or mixture

#### **GHS Classification**

Flammable liquids (Category 2)

Acute toxicity, Oral (Category 2)

Skin corrosion/irritation (Category 2)

Serious eye damage/eye irritation (Category 2A)

Acute aquatic toxicity (Category 3)

Specific target organ toxicity - single exposure (Category 3)

#### 2.2 GHS Label elements, including precautionary statements

Pictogram

Signal word Danger

Hazard statement(s)

H225 Highly flammable liquid and vapour.

H300 Fatal if swallowed. H315 Causes skin irritation.

H319 Causes serious eye irritation.





\_\_\_\_

H402	Harmful to aquatic life.

#### Precautionary statement(s)

P210	Keep away from heat, hot surfaces, sparks, open flames and other
	investiga paramaga. Na propilira

ignition sources. No smoking.

P233 Keep container tightly closed.

P240 Ground and bond container and receiving equipment.

P241 Use explosion-proof electrical/ ventilating/ lighting/ equipment.

P242 Use non-sparking tools.

P243 Take action to prevent static discharges.

P261 Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.

P264 Wash skin thoroughly after handling.

P270 Do not eat, drink or smoke when using this product.

P273 Avoid release to the environment.

P280 Wear eye protection/ face protection. Wear protective gloves.

P301 + P310 + P330 IF SWALLOWED: Immediately call a POISON CENTER/doctor. Rinse

mouth.

P302 + P352 IF ON SKIN: Wash with plenty of water.

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing.

Rinse skin with water.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing.

P332 + P313 If skin irritation occurs: Get medical advice/ attention.
P337 + P313 If eye irritation persists: Get medical advice/ attention.

P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to

extinguish.

P403 + P235 Store in a well-ventilated place. Keep cool.

P405 Store locked up.

P501 Dispose of contents/ container to an approved waste disposal plant.

#### 2.3 Hazards not otherwise classified (HNOC) or not covered by GHS

#### **Target Organs**

Damage to the heart, liver, nervous system, kidney, bone, gastrointestinal tract, teeth, lungs.

#### **SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS**

#### 3.1 Substances

Substance name : ACS Material Upconverting Nanoparticles Formula : NaYREF<sub>4</sub>(RE: Yb, Er, Tm, Gd, Mn, Lu)

Substance : Ethanol
Synonyms : Ethyl alcohol
CAS-No. : 64-17-5
EC-No. : 200-578-6
Molecular weight : 46.07 g/mol
Formula : C<sub>2</sub>H<sub>6</sub>O





Substance : Sodium fluoride CAS-No. : 7681-49-4

EC-No. : 231-667-8 Molecular weight : 41.99 g/mol

Formula : NaF

## **Hazardous components**

Component	Concentration	CAS-No.
Ethanol	99.9 wt %	64-17-5
Sodium fluoride	< 0.1 wt %	7681-49-4
Yttrium	< 0.1 wt %	7440-65-5
Ytterbium	< 0.1 wt %	7440-64-4
Erbium	< 0.1 wt %	7440-52-0
Thulium	< 0.1 wt %	7440-30-4
Gadolinium	< 0.1 wt %	7440-54-2
Manganese	< 0.1 wt %	7439-96-5
Lutetium	< 0.1 wt %	7439-94-3

For the full text of the phrases mentioned in this Section, see Section 16.

Hazardous impurities: None known.

#### **SECTION 4: FIRST AID MEASURES**

#### 4.1 Description of first aid measures

#### **General advice**

Consult a physician. Show this safety data sheet to the doctor in attendance. Move out of dangerous area.

#### If inhaled

If inhaled, remove to fresh air. If not breathing, give artificial respiration. Get medical attention.

#### In case of skin contact

Wash off with soap and plenty of water. Take victim immediately to hospital. Consult a physician. First treatment with calcium gluconate paste.

#### In case of eye contact

In case of contact, immediately flush eyes with plenty of water for at least 15 minutes and consult a physician.

#### If swallowed

Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Rinse mouth with water. Consult a physician.

## 4.2 Most important symptoms and effects, both acute and delayed



## Safety Data Sheet – Upconverting Nanoparticles ACS Material LLC

The most important known symptoms and effects are described in the labelling (see section 2.2) and/or in section 11.

4.3 Indication of any immediate medical attention and special treatment needed No data available.

#### **SECTION 5: FIREFIGHTING MEASURES**

#### 5.1 **Extinguishing media**

#### Suitable extinguishing media

Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.

#### 5.2 Hazards arising from the substance or mixture

Hazardous decomposition products formed under fire conditions. - Carbon oxides, hydrogen fluoride, sodium oxides, yttrium oxides, ytterbium oxides, erbium oxides, gadolinium oxides, manganese/manganese oxides.

#### **Advice for firefighters** 5.3

Wear self-contained breathing apparatus for firefighting if necessary.

#### 5.4 **Conditions of flammability**

Flammable in the presence of a source of ignition when the temperature is above the flash point. Keep away from heat/sparks/open flame/hot surface. No smoking.

#### 5.5 **Further information**

Use water spray to cool unopened containers...

#### **SECTION 6: ACCIDENTAL RELEASE MEASURES**

#### 6.1 Personal precautions, protective equipment and emergency procedures

Use personal protective equipment. Avoid breathing vapours, mist or gas. Ensure adequate ventilation. Remove all sources of ignition. Evacuate personnel to safe areas. Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.

For personal protection see section 8.

#### 6.2 **Environmental precautions**

Prevent further leakage or spillage if safe to do so. Do not let product enter drains.

#### Methods and materials for containment and cleaning up 6.3

Sweep up and shovel. Contain spillage, and then collect with an electrically protected vacuum cleaner or by wet-brushing and place in container for disposal according to local regulations (see section 13).

#### 6.4 Reference to other sections

Keep in suitable, closed containers for disposal. For disposal see section 13.

#### **SECTION 7: HANDLING AND STORAGE**



### 7.1 Precautions for safe handling

Avoid contact with skin and eyes. Avoid inhalation of vapour or mist.

Use explosion-proof equipment. Keep away from sources of ignition - No smoking. Take measures to prevent the build up of electrostatic charge.

For precautions see section 2.2.

#### 7.2 Conditions for safe storage, including any incompatibilities

Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Do not store near acids. Hygroscopic. Keep at 4-8 °C. Light, and moisture sensitive.

#### 7.3 Specific end use(s)

Apart from the uses mentioned in section 1.2 no other specific uses are stipulated.

#### **SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION**

## 8.1 Control parameters

#### **Components with workplace control parameters**

Components	CAS-No.	Value	Control Parameters	Basis
Ethanol	64-17-5	TWAEV	1,000.000000 ppm 1,900.000000 mg/m <sup>3</sup>	Canada. Ontario OELs
		TWA	1,000.000000 ppm 1,880.000000 mg/m <sup>3</sup>	Canada. Alberta, Occupational Health and Safety Code (table 2: OEL)
		TWAEV	1,000 ppm 1,880 mg/m <sup>3</sup>	Québec. Regulation respecting occupational health and safety, Schedule 1, Part 1: Permissible exposure values for airborne contaminants
		STEL	1,000.000000 ppm	Canada. British Columbia OEL
		TWA	1,000.000000 ppm	Canada. British Columbia OEL
		TWA	1,000.000000 ppm	USA. ACGIH Threshold Limit Values (TLV)
		STEL	1,000.000000 ppm	USA. ACGIH Threshold Limit Values (TLV)
Sodium fluoride	7681-49-4	TWA	2.500000 mg/m <sup>3</sup>	Canada. Alberta, Occupational Health and Safety Code (table 2: OEL)





# **ACS Material LLC**

		•		
		TWAEV	2.500000 mg/m <sup>3</sup>	Canada. Ontario OELs
		TWA	2.500000 mg/m <sup>3</sup>	Canada. British Columbia OEL
		TWA	2.500000 mg/m <sup>3</sup>	Québec. Regulation respecting occupational health and safety, Schedule 1, Part 1: Permissible exposure values for airborne contaminants
		TWAEV	2.5 mg/m <sup>3</sup>	Québec. Regulation respecting occupational health and safety, Schedule 1, Part 1: Permissible exposure values for airborne contaminants
		TWA	2.500000 mg/m <sup>3</sup>	USA. ACGIH Threshold Limit Values (TLV)
Yttrium	7440-65-5	TWA	1 mg/m <sup>3</sup>	Canada. Alberta, Occupational Health and Safety Code (table 2: OEL)
		TWA	1 mg/m <sup>3</sup>	Canada. British Columbia OEL
		TWAEV	1 mg/m <sup>3</sup>	Canada. Ontario OELs
		TWAEV	1 mg/m <sup>3</sup>	Québec. Regulation respecting occupational health and safety, Schedule 1, Part 1: Permissible exposure values for airborne contaminants
		TWA	1 mg/m <sup>3</sup>	USA. ACGIH Threshold Limit Values (TLV)
Manganese	7439-96-5	TWAEV	1.000000 mg/m <sup>3</sup>	Québec. Regulation respecting occupational health and safety, Schedule 1, Part 1: Permissible exposure values for airborne contaminants
		STEV	3.000000 mg/m <sup>3</sup>	Québec. Regulation respecting occupational health and safety, Schedule 1, Part 1: Permissible exposure values for airborne contaminants
		TWAEV	0.200000 mg/m <sup>3</sup>	Canada. Ontario OELs
		TWAEV	5 mg/m <sup>3</sup>	Québec. Regulation respecting occupational health and safety, Schedule 1, Part 1: Permissible exposure values for airborne contaminants



	100
w	
П	

	TWA	0.200000 mg/m <sup>3</sup>	Canada. Alberta, Occupational Health and Safety Code (table 2: OEL)
	TWA	0.200000 mg/m <sup>3</sup>	Canada. British Columbia OEL
Remarks	Adverse reproductive effect.		
	TWA	0.020000 mg/m <sup>3</sup>	USA. ACGIH Threshold Limit Values (TLV)
	TWA	0.100000 mg/m <sup>3</sup>	USA. ACGIH Threshold Limit Values (TLV)
	TWA	0.200000 mg/m <sup>3</sup>	USA. ACGIH Threshold Limit Values (TLV)

#### 8.2 Exposure controls

Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes and clothing. Wash hands before breaks and immediately after handling the product.

## **Appropriate engineering controls**

Use mechanical exhaust or laboratory fumehood to avoid exposure.

#### Personal protective equipment

#### **Eye/face protection**

Use equipment for eye protection, face shield and safety glasses tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU).

#### Skin protection

Handle with gloves. Gloves must be inspected prior to use. Use proper glove removal technique (without touching glove's outer surface) to avoid skin contact with this product. Dispose of contaminated gloves after use in accordance with applicable laws and good laboratory practices. Wash and dry hands.

#### **Body Protection**

Impervious clothing, Flame retardant antistatic protective clothing. The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.

#### **Respiratory protection**

Where risk assessment shows air-purifying respirators are appropriate use a full-face respirator with multi-purpose combination (US) or type ABEK (EN 14387) respirator cartridges as a backup to engineering controls. If the respirator is the sole means of protection, use a full-face supplied air respirator. Use respirators and components tested and approved under appropriate government standards such as NIOSH (US) or CEN (EU).

#### Control of environmental exposure

Do not let product enter drains.

#### **SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES**



### 9.1 Information on basic physical and chemical properties

1) Appearance Form: Dispersion Colour: Ivory white

2) Odour Odourless

3) Odour Threshold4) pHNo data availableNo data available

5) Melting point/freezing point Melting point/range: -114 °C (-173 °F)

6) Initial boiling point and boiling range 78 °C (172 °F)

7) Flash point 14.0 °C (57.2 °F) - closed cup

8) Evaporation rate No data available

9) Flammability (solid, gas) May be combustible at very high temperature

10) Upper/lower flammability or explosive Upper explosive limit: 19 %(V) limits Upper explosive limit: 3.3 %(V)

11) Vapour pressure 59.5 hPa (44.6 mmHg) at 20.0 °C (68.0 °F)

12) Vapour density No data available

13) Relative density 0.789 g/cm<sup>3</sup> at 25 °C (77 °F)

14) Water solubility Completely soluble

15) Partition coefficient: n- octanol/water log Pow: -0.349 at 24 °C (75 °F)

16) Auto-ignition temperature
 17) Decomposition temperature
 363 °C (685 °F)
 No data available

18) Viscosity19) Explosive propertiesNo data availableNo data available

20) Oxidizing properties No data available

#### 9.2 Other safety information

No data available.

#### **SECTION 10: STABILITY AND REACTIVITY**

## 10.1 Reactivity

No data available.

#### 10.2 Chemical stability

Stable under recommended storage conditions.

#### 10.3 Possibility of hazardous reactions

Vapours may form explosive mixture with air.

#### 10.4 Conditions to avoid

Heat, spark and flame. Extremes of temperature and direct sunlight.

## 10.5 Incompatible materials

Alkali metals, oxidizing agents, peroxides, strong acids, halogens, oxygen, phosphorus, sulphur oxides.



## **→** Safety Data Sheet – Upconverting Nanoparticles

#### 10.6 Hazardous decomposition products

Hazardous decomposition products formed under fire conditions. - Carbon oxides, hydrogen fluoride, sodium oxides, ytterbium oxides, erbium oxides, gadolinium oxides, manganese/manganese oxides.

Other decomposition products - Gaseous hydrogen fluoride (HF).

In the event of fire: see section 5.

#### **SECTION 11: TOXICOLOGICAL INFORMATION**

#### 11.1 Information on toxicological effects

#### **Acute toxicity**

LD50: No data available.

LC50: No data available.

Dermal: No data available.

Intravenous - Rat - Nutritional and Gross Metabolic: Weight loss or decreased weight gain.

#### Skin corrosion/irritation

Irritating to skin.

## Serious eye damage/eye irritation

Eyes - Rabbit - Moderate eye irritation.

#### Respiratory or skin sensitisation

No data available.

#### Germ cell mutagenicity

No data available.

#### Carcinogenicity

Carcinogenicity - Mouse - Oral

Carcinogenicity - Rat - Intramuscular

Tumorigenic: Equivocal tumorigenic agent by RTECS criteria. Liver: Tumors.

Blood: Lymphomas including Hodgkin's disease.

IARC: No component of this product present at levels greater than or equal to 0.1% is

identified as probable, possible or confirmed human carcinogen by IARC.

#### Reproductive toxicity

Reproductive toxicity - Human - female - Oral

Effects on Newborn: Apgar score (human only). Effects on Newborn: Other neonatal measures or effects. Effects on Newborn: Drug dependence.

#### Specific target organ toxicity - single exposure

No data available.

#### Specific target organ toxicity - repeated exposure

No data available.

## **Aspiration hazard**

No data available.





**Inhalation** May be harmful if inhaled. Causes respiratory tract irritation. Vapours

may cause drowsiness and dizziness.

**Ingestion** May be fatal if swallowed. Aspiration hazard if swallowed – can enter

lungs and cause damage.

**Skin** May be harmful if absorbed through skin. May cause skin irritation.

**Eyes** Causes eye irritation.

## Signs and Symptoms of Exposure

Central nervous system depression, narcosis, Damage to the heart., To the best of our knowledge, the chemical, physical, and toxicological properties have not been thoroughly investigated. Fluoride ion can reduce serum calcium levels possibly causing fatal hypocalcemia. Rare earth compounds may cause delayed blood clotting leading to hemorrhages. Inhalation of rare earths may cause sensitivity to heat, itching, and increased awareness of odor and taste.

#### **Additional Information**

RTECS: KQ6300000(Ethanol).

To the best of our knowledge, the chemical, physical, and toxicological properties have not been thoroughly investigated.

#### **SECTION 12: ECOLOGICAL INFORMATION**

#### 12.1 Toxicity

No data available.

#### 12.2 Persistence and degradability

No data available.

#### 12.3 Bioaccumulative potential

Bioaccumulation - Salmo trutta

#### 12.4 Mobility in soil

No data available.

#### 12.5 Results of PBT and vPvB assessment

No data available.

#### 12.6 Other adverse effects

Harmful to aquatic life.

#### **SECTION 13: DISPOSAL CONSIDERATIONS**

#### 13.1 Waste treatment methods

#### **Product**

Burn in a chemical incinerator equipped with an afterburner and scrubber but exert extra care



## Safety Data Sheet – Upconverting Nanoparticles

**ACS Material LLC** 

in igniting as this material is highly flammable. Offer surplus and non-recyclable solutions to a licensed disposal company. Contact a licensed professional waste disposal service to dispose of this material.

### Contaminated packaging

Dispose of as unused product.

#### **SECTION 14: TRANSPORT INFORMATION**

**UN** number

ADR/RID: 1170 IMDG: 1170 IATA: 1170

**UN proper shipping name** 

ADR/RID: Ethanol. IMDG: ETHANOL. IATA: Ethanol.

Transport hazard class(es)

ADR/RID: 3 IMDG: 3 IATA: 3

Packaging group

ADR/RID: - IMDG: - IATA: -

**Environmental hazards** 

ADR/RID: no IMDG Marine pollutant: no IATA: no

Special precautions for user

No data available.

#### **SECTION 15: REGULATORY INFORMATION**

# 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

# Authorisations and/or restrictions on use WHMIS Classification

B2	Flammable liquid	Flammable liquid
D1B	Toxic Material Causing Immediate and	Toxic by ingestion

Serious Toxic Effects

D2A Very Toxic Material Causing Other Reproductive hazard

**Toxic Effects** 

D2B Toxic Material Causing Other Toxic Moderate skin irritant

Effects Moderate eye irritant

#### **SECTION 16: OTHER INFORMATION**

#### **HMIS Classification**

Health hazard: 2
Chronic Health Hazard: \*
Flammability: 3
Physical Hazard: 0



**Disclaimer:** ACS Material, LLC believes that the information in this Safety Data Sheet is accurate and represents the best and most current information available to us. ACS Material makes no representations or warranties either express or implied, regarding the suitability of the material for any purpose or the accuracy of the information contained within this document. Accordingly, ACS Material will not be responsible for damages resulting from use of or reliance upon this information.

