

Technical Data Sheet

ACS Material FlashVoltTM Joule Heating Test Service

Contact Information:

ACS Material, LLC

Address: 959 E Walnut St., Suite 100

Pasadena, CA 91106, USA

Phone: (866)-227-0656

Fax: (781)-518-0284

E-Mail: contact@acsmaterial.com


Revision: 020524

Joule Heating Capabilities

Equipment	FlashVolt TM Joule Heating System
Equipment Model	Model A (FVJH-V1-A) and Model B (FVJH-V1-B)
Materials	Powder, Film, Bulk, Gel
Experimental Conditions	Flash Evaporation, Pulse Discharge, Staged Heating, Discharge Composite
Test Atmosphere	Air, Argon, Vacuum
Application Field	Ceramics, Nanoparticles, Sustainability, Graphene, Catalyst

^{*}Powder samples: Each experiment typically involves a quantity ranging from 0.1g to 1.5g. Different experimental conditions often requires multiple attempts, if the sample is not extremely valuable, it is advisable to send a larger amount, preferably at least 5g.

^{*}For bulk/film samples, the length should be 40mm or more.



Disclaimer: ACS Material, LLC believes that the information in this Technical Data Sheet is accurate and represents the best and most current information available to us. ACS Material makes no representations or warranties either express or implied, regarding the suitability of the material for any purpose or the accuracy of the information contained within this document. Accordingly, ACS Material will not be responsible for damages resulting from use of or reliance upon this information.