



## ACS Material Equipment Series

### Mini Banbury Mixer

**Contact Information:**

ACS Material, LLC

Address: 959 E Walnut St., Suite 100

Pasadena, CA 91106, USA

Phone: (866)-227-0656

Fax: (781)-518-0284

E-Mail: [contact@acsmaterial.com](mailto:contact@acsmaterial.com)

Revision: 082724

## Product Overview

Our detachable Mini Internal Mixer adapts for fast electrical heating (by heating rod) as well as air cooling with accurate temperature and rotor speed controls. The compact mixer chamber has a detachable structure, which makes it easy to quickly and conveniently disassemble and clean the material thoroughly. This versatile equipment can be used to study formulations and properties of rubber, plastic and other materials, and can also be useful for researching and developing formulas for entirely new materials.



## Product Features

- Lightweight (about 85kg) and compact structure
- Easy to disassemble and provides easy access for thorough material cleaning. Can enter the fume hood.
- Rotor speed can be regulated (stepless)
- Temperature up to 450°C; can be controlled during mixing

- Water cooling
- Torque curve display
- Can mix rubber, plastic and other materials (such as tires, rubber tubes, PVC, carbon black, various cable materials, etc)

### Product Specifications

Product Name	Mini Internal Mixer, Model: 36C	Mini Internal Mixer, Model: 36D	Mini Internal Mixer, Model: 70C	Mini Internal Mixer, Model: 70D
SKU#	EIMM36C1	EIMM36D1	EIMM70C1	EIMM70D1
Model#	36C	36D	70C	70D
Rotor Speed (RPM) (continuous adj ustable)	60	60	60	60
Maximum Torque (NM)	60	60	60	60
Mixer Capacity (ml per batch)	<b>36</b>	<b>36</b>	<b>70</b>	<b>70</b>
Cooling Method	<b>Water cooling</b>	<b>Water cooling</b>	<b>Water cooling</b>	<b>Water cooling</b>
Temperature Display Accuracy	+/-1 %	+/-1 %	+/-1 %	+/-1 %
Temperature Range (°C)	40-300	40-450	40-300	40-450
Voltage Supply (V)	240	240	240	240
Overall Size W x D x H (mm)	700×400×300	700×400×300	700×400×300	700×400×300
Weight (kg)	85	85	85	85
Equipment Power (KW)	2.2	2.2	2.2	2.2
Curve Display Rheometer	LCD	LCD	LCD	LCD

**Disclaimer:** ACS Material, LLC believes that the information in this Technical Data Sheet is accurate and represents the best and most current information available to us. ACS Material makes no representations or warranties either express or implied, regarding the suitability of the material for any purpose or the accuracy of the information contained within this document. Accordingly, ACS Material will not be responsible for damages resulting from use of or reliance upon this information.